Technical Specifications

Power supply	19.3 ... 30VDC
Power consumption	typ. 0.32W
Belimo MP-Bus Interface	MPL devices exclusive: up to 16 MP-Bus devices mixed: up to 8
Loxone Air	Wireless connection with Miniserver / Air Base Extension internal antenna
Power loss at max. load	0.41W

Ambient conditions

Ambient temperature	-20 ... +70°C / -4...158°F
Humidity	max. 95% r.H. (non condensing)
Degree of Protection	IP20

About the product

Belimo is one of the leading manufacturers of drives in the area of climate control. Belimo Air is an interface to integrate up to 16 Belimo MP-Bus devices. With the native MP-Bus integration Belimo products become a native member of Loxone Config and the Miniserver.

For more information about this product, visit **loxone.com/help/belimo-air**

LOXONE

Loxone Electronics GmbH
Smart Home 1
4154 Kollerschlag
Austria

Loxone UK
The Forum
Station Road
Theale, RG7 4RA
United Kingdom

Belimo Air

For additional information, declaration of conformity, visit **www.loxone.com/datasheets**

V181022

Need Help?
loxone.com/support

UK CA CE

Part No.: 100520

Connecting Terminals

DC Supply

Terminal type	DG220B
Wire cross-section	0.28 ... 0.8mm² / AWG23 ... 18
Stripping length	5 … 6mm / 0.2 … 0.24"

MP-Bus

Terminal type	Connecting lead with open end
Wire cross-section	1.5mm² / AWG18
Length	150mm / 5.91"

MP-BUS®
MP-BUS® COMPATIBLE